



BAUDOQUIN

Technical Specifications



ENGINE

- BAUDOQUIN series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air charge cooled /turbocharged & air to water charge cooled
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000, IEC 34, TS ISO 8528, TS EN ISO 3744, TS EN ISO 3746, TS EN 60034-1, TS EN 60204-1, TS EN 60335-1, TS EN 61439-1, EN 61000, TS EN ISO12100 standards.

We have ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 and ISO10002:2006 management system certificates from Kiwa & MEYER, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid.

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Battery charger
- Hardware and materials needed
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start/stop failure



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender





BAUDOUIIN Series Diesel Generator Sets 90-120-150-165 kVA

MODEL				ABJ-90	ABJ-120	ABJ-150	ABJ-165
GROUP	GEN-SET POWER	STAND BY	kVA	90	120	150	165
			kW	72	96	120	132
		PRIME	kVA	81,8	109	135	150
			kW	65,5	87,2	108	120
	CANOPY DIMENSION (W x L x H) mm			1100x2750x1700	1100x2750x1700	1100x3050x1700	1100x3050x1700
	CANOPY WEIGHT kg			1600	1750	1800	2050
	OPEN DIMENSION (W x L x H) mm			1100x2300x1450	1100x2300x1450	1100x2600x1450	1100x2600x1450
	OPEN WEIGHT			1250	1400	1450	1650
ENGINE	BRAND			BAUDOUIIN	BAUDOUIIN	BAUDOUIIN	BAUDOUIIN
	TYPE			4M11G90/5	4M11G120/5	6M11G150/5	6M11G165/5
	POWER	STAND BY	kW	81	108	140	152
		PRIME	kW	73,6	98	127	138
	SPEED (rpm)			1500	1500	1500	1500
	CYCLE			4	4	4	4
	DISPLACEMENT (lt)			4,5	4,5	6,75	6,75
	NUMBER OF CYLINDERS			4 IN LINE	4 IN LINE	6 IN LINE	6 IN LINE
	BORE x STROKE (mm x mm)			105 x 130	105 x 130	105 x 130	105 x 130
	COMPRESSION RATIO			18 : 1	18 : 1	18 : 1	18 : 1
	GOVERNOR TYPE			ELECTRONIC	ELECTRONIC	ELECTRONIC	ELECTRONIC
	INDUCTION			TURBOCHARGED-AIR TO AIR COOLED			
	COMBUSTION SYSTEM			DIRECT	DIRECT	DIRECT	DIRECT
	COOLING SYSTEM			WATER	WATER	WATER	WATER
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		17,8	23,2	30,4	32,7
		%75 PRIME POWER		13,3	17,4	23,1	24,5
%50 PRIME POWER		9,2	11,9	15,9	16,7		
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			10	10	16	16	
TOTAL COOLANT CAPACITY (lt)			15,3	15,3	28	28	
FUEL TANK CAPACITY (lt)			200	200	240	240	

Armak reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

Armak Makine Mühendislik İnş. San. ve Tic. Ltd. Şti.

Denizköşkler Mah. Tunay Sk. No:28
Avcılar / İSTANBUL / TURKEY

T: 0212 694 66 66

F: 0212 593 09 60

armakmakine@armakmakine.com

www.armakmakine.com