



ARMAC

J E N E R A T Ö R



PERKINS

Technical Specifications



ENGINE

- PERKINS series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air COOLED /turbocharged & air to water COOLED
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000, IEC 34, TS ISO 8528, TS EN ISO 3744, TS EN ISO 3746, TS EN 60034-1, TS EN 60204-1, TS EN 60335-1, TS EN 61439-1, EN 61000, TS EN ISO12100 standards.

We have ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 and ISO10002:2006 management system certificates from Kiwa & MEYER, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid.

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Over current load
- Low oil pressure
- High & low genset voltage
- High & low engine speed
- Start/stop failure
- Low radiator water level



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender





PERKINS Series Diesel Generator Sets 650-825 kVA

MODEL				APJ - 660	APJ - 725	APJ - 785	APJ - 825
GROUP	GEN-SET POWER	STAND BY	kVA	660	725	785	825
			kW	528	580	628	660
		PRIME	kVA	600	659	715	750
			kW	480	527	572	599
	CANOPY DIMESNION (W x L x H) mm			1700x4400x2860	1700x4400x2860	1800x4800x3115	1800x4800x3115
	CANOPY WEIGHT kg			6298	6440	8817,5	8817,5
	OPEN DIMENSION (W x L x H) mm			1700x3500x2160	1700x3500x2160	1800x4290x2475	1800x4290x2475
	OPEN WEIGHT			5641	5783	7310,5	7310,5
ENGINE	BRAND			PERKINS	PERKINS	PERKINS	PERKINS
	TYPE			2806A-E18TAG1A	2806A-E18TAG2	2806A-E18TAG4	2806A-E18TTAG5
	POWER	STAND BY	kW	574	609	685	739
		PRIME	kW	522	565	623	671
	SPEED (rpm)			1500	1500	1500	1500
	CYCLE			4	4	4	4
	DISPLACEMENT (lt)			18,1	18,1	18,1	18,1
	NUMBER OF CYLNDERS			6 IN LINE	6 IN LINE	6 IN LINE	6 IN LINE
	BORE x STROKE (mm x mm)			145 x 183	145 x 183	145 x 183	145 x 183
	COMPRESSION RATIO			14,5 : 1	14,5 : 1	14 : 1	14 : 1
	GOVERNOR TYPE			ELECTRONIC	ELECTRONIC	ELECTRONIC	ELECTRONIC
	INDUCTION			TURBOCHARGED - AIR TO AIR COOLED	TURBOCHARGED - AIR TO AIR COOLED	TURBOCHARGED - AIR TO AIR COOLED	TURBOCHARGED - AIR TO AIR COOLED
	COMBUSTION SYSTEM			DIRECT	DIRECT	DIRECT	DIRECT
	COOLING SYSTEM			WATER	WATER	WATER	WATER
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		123	132	143	162
		%75 PRIME POWER		90	97	105	118
		%50 PRIME POWER		61	66	72	80
TOTAL LUBRICATION SYSTEM CAPACITY (lt)			62	62	68	110	
TOTAL COOLANT CAPACITY (lt)			61	61	110	68	
FUEL TANK CAPACITY (lt)			980	980	1704	1704	

Armak reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

Armak Makine Mühendislik İnş. San. ve Tic. Ltd. Şti.

Denizköşkler Mah. Tunay Sk. No:28
Avcılar / İSTANBUL / TURKEY

T: 0212 694 66 66

F: 0212 593 09 60

armakmakine@armakmakine.com

www.armakmakine.com