



VOLVO

Technical Specifications



ENGINE

- VOLVO series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged & air to air charge cooled /turbocharged & air to water charge cooled
- Direct injection
- Electronic governor system
- 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extension pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine block water heater (in automatic models)
- Diesel gen-set maintenance and operating instructions and electrical circuit diagram

QUALITY STANDARD

Our generators are manufactured in compliance with VDE 0530, BSE 4999 BS5000, IEC 34, TS ISO 8528, TS EN ISO 3744, TS EN ISO 3746, TS EN 60034-1, TS EN 60204-1, TS EN 60335-1, TS EN 61439-1,

EN 61000, TS EN ISO12100 standards.

We have ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 and ISO10002:2006 management system certificates from Kiwa & MEYER, an accredited independent quality organization.

Our generators up to 400 kw are manufactured in compliance with 2000/14/EC European noise emission directive and certified from Ente Certificazione Macchine.

We also have TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 flame retardancy and TS EN ISO 9227 certificates against anti-corrosion together with CE Declaration.

ALTERNATOR

- Brushless, single bearing, flexible disc 4 poles alternator for harmonic failure
- H type isolation class
- IP 21-23 protection class
- Self exciter
- Electronic automatic voltage regulator
- Stator 2/3 step for harmonic failure
- The alternator windings are protected by insulating varnish against oil and acid.

EXTRA EQUIPMENTS

- Charge ammeter
- Moulded case circuit breaker (in automatic models)
- Hospital/Critical type silencer
- Sound-proof canopy
- Mobile - trailer
- Synchronization control panel for 2-16 gensets
- 3 pole/4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel-water separator filter
- PMG warning system

CANOPY

- Modular type sound-proof canopy
- Canopy installation executed with screw and nut, without welding process
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Lockable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

AUTOMATIC CONTROL PANEL

- LCD display screen
- Battery charger
- Hardware and materials needed
- USB port & RS-485 output

GEN-SET SAFETY PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start/stop failure



Easy maintenance canopy design



Refilling from the outside of the canopy



Canopy made of galvanized steel



Warning system for decreasing fuel with electronic fuel level sender





ARMAK

J E N E R A T Ö R



VOLVO Series

Diesel Generator Sets

VOLVO Series Diesel Generator Sets 94 -110 -145 -167 -200 -225 kVA

MODEL				AVJ - 094	AVJ - 0110	AVJ - 0145	AVJ - 0167	AVJ - 0200	AVJ - 0225	
GROUP	GEN-SET POWER	STAND BY	kVA	94	110	145	167	200	225	
			kW	76	88	116	133	160	180	
		PRIME	kVA	85	100	132	152	181,8	204,5	
			kW	68	80	105,5	121	145,5	163,6	
	CANOPY DIMESNION (W x L x H) mm			1100x2900x1800	1100x2900x1800	1100x2900x1800	1100x3200x1800	1300x3600x2050	1300x3600x2050	
	CANOPY WEIGHT kg			1550	1600	1650	2150	2450	2550	
	OPEN DIMENSION (W x L x H) mm			1100x2200x1600	1100x2200x1600	1100x2200x1600	1100x2500x1600	1300x2900x1800	1300x2900x1800	
	OPEN WEIGHT			1300	1350	1400	1750	2100	2200	
ENGINE	BRAND			VOLVO	VOLVO	VOLVO	VOLVO	VOLVO	VOLVO	
	TYPE			TAD 530 GE	TAD 531 GE	TAD 532 GE	TAD 731 GE	TAD 732 GE	TAD 733 GE	
	POWER	STAND BY	kW	83	98	125	148	179	195	
		PRIME	kW	74	88	112	133	160	175	
	SPEED (rpm)			1500	1500	1500	1500	1500	1500	
	CYCLE			4	4	4	4	4	4	
	DISPLACEMENT (lt)			4,76	4,76	4,76	7,15	7,15	7,15	
	NUMBER OF CYLNDERS			4 IN LINE	4 IN LINE	4 IN LINE	6 IN LINE	6 IN LINE	6 IN LINE	
	BORE x STROKE (mm x mm)			108 x 130	108 x 130	108 x 130	108 x 130	108 x 130	108 x 130	
	COMPRESSION RATIO			18 : 1	18 : 1	17,5 : 1	18 : 1	18 : 1	18,1 : 1	
	GOVERNOR TYPE			ELECTRONIC	ELECTRONIC	ELECTRONIC	ELECTRONIC	ELECTRONIC	ELECTRONIC	
	INDUCTION			TURBOCHARGED - AIR TO AIR	TURBOCHARGED - AIR TO AIR	TURBOCHARGED - AIR TO AIR	TURBOCHARGED - AIR TO AIR	TURBOCHARGED - AIR TO AIR	TURBOCHARGED - AIR TO AIR	
	COMBUSTION SYSTEM			DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	DIRECT	
	COOLING SYSTEM			WATER	WATER	WATER	WATER	WATER	WATER	
	FUEL CONSUMPTION lt / h	%100 PRIME POWER			19,12	22,84	28,53	34,04	40,57	45
		%75 PRIME POWER			14,47	17,13	21	25,65	30,43	33,44
		%50 PRIME POWER			10,18	11,78	14,2	17,73	20,86	22,6
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			13	13	13	20	34	34	
	TOTAL COOLANT CAPACITY (lt)			19,7	19,7	19,7	23,8	37	38	
	FUEL TANK CAPACITY (lt)			220	220	220	280	365	365	

Armak reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

Armak Makine Mühendislik İnş. San. ve Tic. Ltd. Şti.

Denizköşkler Mah. Tunay Sk. No:28
Avcılar / İSTANBUL / TURKEY

T: 0212 694 66 66

F: 0212 593 09 60

armakmakine@armakmakine.com

www.armakmakine.com